

**SPECIFICATION:**





JOSAM 76000 SERIES COATED CAST IRON RECTANGULAR SECTIONAL TRENCH DRAIN WITH HEAVY-DUTY BODY SECTIONS AND INTEGRAL ANCHOR FLANGE, HEAVY-DUTY LOOSE-SET SUPER-FLO GRATES WITH PERIMETER DRAINAGE SLOTS, SECONDARY LOOSE-SET DOME STRAINER AND BOTTOM INSIDE CAULK OUTLET CONNECTION.

**TRENCH DRAIN  
SUPER-FLO 6" WIDE,  
RECTANGULAR**

SERIES **76000**

MEETS ADA AND HEEL-PROOF REQS.  
SLOT WIDTH 3-1/2" X 5/16"  
(-1 AND -2 SLOT WIDTH 1-11/16 X 1/4")

ASSEMBLY SHOWN AS EXAMPLE ONLY



PRODUCT IS NON-CANCELABLE  
AND NON-RETURNABLE

NAME: \_\_\_\_\_

SIGNATURE: \_\_\_\_\_

DATE: \_\_\_\_\_

\* THESE OPTIONS REQUIRE  
SIGNATURE - NON CANCELABLE  
NON RETURNABLE

IT IS RECOMMENDED THAT NO MORE  
THAN EIGHT (8) EXTENSION SECTIONS BE  
USED WITH ONE (1) OUTLET SECTION

ADD 1/4" FOR NIKALOY OR BRONZE TOP  
ALSO ADD 1/4" TO OVERALL LENGTH

-EXT	EXTENSION SECTION
-1	SATIN FINISH NIKALOY TOP
-2	SATIN FINISH BRONZE TOP
-7	DUCTILE IRON GRATE
-30	FLASHING CLAMP DEVICE
-40	GALVANIZED CAST IRON PARTS
-VP*	SECURED GRATE-VANDAL-PROOF SCREWS
-ARE*	ACID RESISTANT EPOXY COATING

	PIPE SIZE
	2"
	3"
	4"

FOR INSTALLATIONS EXPOSED TO VEHICULAR  
TRAFFIC, SPECIFY -VP SECURED GRATE OPTION

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

DATE OF LAST CHANGE: 02/27/25 BLK

DIMENSIONS ARE SUBJECT TO MANUFACTURERS  
TOLERANCES AND CHANGE WITHOUT NOTICE.  
WE CAN ASSUME NO RESPONSIBILITY FOR  
USE OF SUPERSEDED OR VOID DATA.



NOTES