SPECIFICATIONS

42440 SS Drain 8" Round Top, 8" Deep Specification

Josam series 42440 stainless steel (Type 304), 8" round top, 8" deep, with no-hub bottom outlet, anchor tabs and perforated SS grate (standard).

De ub tted B Ø 7 13/16 [198] ↓ 11/8 ↓ 11/8 ↓ 11/8 ↓ 11/8



STANDARD GRATE FREE AREA = 18.4 IN²





-FBFilter basketNGNo grate-SBSediment bucketHGPerf. half grate-VPSecured grate-3QPerf. 3/4 grate-SOSide outletMGMesh, anti-slip grate-SO1/2" primer tap-LGLadder grate-TThreaded outlet-SGPerimeter slot grate-316Type 316L material-SKSealed cover w/vacuum handle-FFFlange only-WHWeep holes-CFClamp and flange-DBDome bottom strainer	 		 			
-VP Secured grate -SO Side outlet -SO Side outlet -50 1/2" primer tap -T Threaded outlet -316 Type 316L material -BW Butt-weld outlet (spec. 10, 40, 80) -F Flange only	-FB	Filter basket	-NG	No grate		
-SO Side outlet -50 1/2" primer tap -T Threaded outlet -316 Type 316L material -BW Butt-weld outlet (spec. 10, 40, 80) -F Flange only	-SB	Sediment bucket	-HG	Perf. half grate		
-50 1/2" primer tap -T Threaded outlet -316 Type 316L material -BW Butt-weld outlet (spec. 10, 40, 80) -F Flange only	-VP	Secured grate	-3Q	Perf. 3/4 grate		
-T Threaded outlet -316 Type 316L material -BW Butt-weld outlet (spec. 10, 40, 80) -F Flange only	-SO	Side outlet	-MG	Mesh, anti-slip grate] -	
-316 Type 316L material -BW Butt-weld outlet (spec. 10, 40, 80) -F Flange only -WH Weep holes	-50	1/2" primer tap	-LG	Ladder grate		
-BW Butt-weld outlet (spec. 10, 40, 80) -SV Sealed cover w/vacuum handle -F Flange only -WH Weep holes	-т	Threaded outlet	-SG	Perimeter slot grate]	
-F Flange only -WH Weep holes	-316	Type 316L material	-SK	Sealed cover w/eyebolt key]	
	-BW	Butt-weld outlet (spec. 10, 40, 80)	-SV	Sealed cover w/vacuum handle]	
-CF Clamp and flange -DB Dome bottom strainer	-F	Flange only	-WH	Weep holes]	
	-CF	Clamp and flange	-DB	Dome bottom strainer]	

Model	Pipe size
42442	2"
42443	3"
42444	4"

[25]

Josam product specifications in U.S. customary units are approximate and provided for reference only. For precise measurements, please contact Josam Technical Support. Josam reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Josam products previously or subsequently sold.

Notes:



A WATTS Brand

T: (800) 365-6726 • Josam.com